MEDIA CONVERTER SYSTEM PRODUCTS

DVI to Fiber Converter with USB, SM 20Km, WDM, SC

FEATURE


- Through a one core single mode fiber can transmit oneway DVI video,
- stereo audio, and KVM signals
- Support for up to DVI resolution up to 1080P / 60HZ
- Optical fiber transmission distance up to 20KM
- The device supports DVI, Audio Interface
- Support for KVM, USB mouse and keyboard to remotely control

OCOMM

OVERVIEW

DVI KVM optic converter is a transmission DVI, Audio and fiber optic transmission products keyboard and mouse signals over a single fiber; the host computer's audio, DVI and USB keyboard and mouse interface extendedvia optical fiber to the distal end, the user can listen to the host computer in real time at the distal and sound, and you can use the mouse and keyboard to control the front-end mainframe computer. Support DVI high definition audio and video real-time transmission, a maximum resolution of 1080P / 60HZ; maximum transmission distance up to 20KM, widely used in military command and control, traffic police traffic management, energy and electricity supply industries, government departments, medical systems, trade shows, multimedia function rooms, public utilities and other fields.

TOPOLOGICAL GRAPH



Large screen display device







DESCRIPTION

| Video Audio | Signal Input | All the way DVI, Audio signals |
|--------------|-----------------------------|--|
| | Signal output | All the way DVI, Audio signals |
| | Video input interface | DVI-I interface |
| | Video output interface | DVI-I interface |
| | Maximum video resolution | 1080P/60HZ |
| Optical port | Audio frequency | 3.5mm stereo |
| | Input and output fiber port | FC screw |
| | Transmission distance | 20KM |
| | Transmission wavelength | 1310nm/1550nm |
| USB port | Interface | End computer, mouse, keyboard terminal |
| | Signal Type | KVM (only supports USB mouse and keyboard signals) |
| Other | Input voltage | DC 12V |
| | Power | 3W |
| | Operating temperature | Minus 10 degrees Celsius to 50 degrees above zero |
| | Working humidity | 5% ~ 90% |
| | Physical dimension | 16cm*12cm*3cm |
| | Net weight | 1.2KG / pair |
| | | |

ORDER INFOMATION

| PRODUCT | PART NUMBER |
|---|--------------------|
| DVI to Fiber Converter with USB, SM 20Km, WDM, SC | H-DVIT/R-USB-F9-20 |