

# EPON OLT

EPON OLT , 2 SFP PON ports , 2 x 1000M RJ45 ports and 1 x 10/100M RJ45 ports



## FEATURE

- Supply 2 SFP PON ports, 2 1000M RJ45 ports, 1 10/100M RJ45 management port
- Support SNMP management and WEB management
- Each PON port support 1:32 split ratio, total 64 ONUs access,maximum 128
- Distance can reach 20km under 1:32 split ratio,maximum 1:64
- Support to work with ONUs to establish passive network
- 1U rack design, inside fan,better for heat dissipating and reliability operating
- Apply for town,village fiber network and surveillance, apply for FTTX network, to transmit IP phone, data,IPTV and other IP services access



## OVERVIEW

FO-7302CST is a standalone 2-PON OLT,working series ONU and ODN, to establish a passive optic network. It supports 2-PON, 64 ONUs access (maximum 128). It supports 10~20km transmission distance at the base of high bandwidth, full line speed L2/L3 transition capacity. It supports WEB/SNMP/CLI management.

## APPLICATION

1000M point to multi-point optic passive network

## TECHNICAL SPECIFICATION

Parameter	Specification
Operating wavelength	1310( RX) /1490(TX)
Optical power	+0 ~ +7dBm
Receiving sensitivity	-27dBm
Max distance	20km
Max splitter ratio	1:64
Capacity	2 PON, standard: 64 ONUs maximum:128 ONUs
MAC	8K
Uplink port	2 1000M Ethernet RJ45 ports / 2 Gigabit SFP ports optional
PON port	2 SFP fiber ports
Control port	RJ45 console port, to debug the device
MTBF	100,000 hours
EPON traits	Support IEEE802.3ah Support DBA with minimum1Kbps granularity adjustable Support 1Gbps up link and down link symmetrical bandwidth Support AES-128 encryption to each Logical Link Identifier Support powerful OAM function, implement telnet management, maintenance and upgrade Support auto discovery and auto register of ONU (real-time operation)
Protocols supported	Support IEEE802.3, IEEE802.3u, IEEE802.3ab Support IEEE802.1Q VLAN Support IEEE 802.1P QoS
Management	CLI and GUI, SNMP, WEB Support DHCP Snooping Support Ipv4 address learning based at DHCP Snooping Support ARP Snooping, QoS etc

## WORKING ENVIRONMENT

Parameter	Specification
Power	AC220V
Power consumption	11W
Operating temperature	-10~55°C
Storage temperature	-40~70°C
Humidity	5%~90% non-condensing
Dimension	276mm(length) ×200mm(width) ×44mm(height)

## ORDER INFORMATION

PRODUCT	PART NUMBER
EPON OLT , 2 SFP PON ports , 2 x 1000M RJ45 ports and 1 x 10/100M RJ45 ports	FO-7302CST