

EPON OLT

EPON OLT, layer 3 , 8 PON ports , 4 ports 10G SFP



FEATURE

- Supply 4 SFP PON ports, 8 10/100/1000M TP uplink ports, 4 10G SFP+ uplink ports
- Support L2 and L3 protocol
- Support SNMPv1/v2/v3
- Support IPV4,IPV6
- Support IGMP v1/v2/v3
- Support to work with different chipset solution EPON ONUs
- Built-in double power supply (optional), including AC or DC power



TECHNICAL SPECIFICATION

Parameter	Specification
Switching Capacity	128Gbps
Forwarding Capacity(Ipv4/Ipv6)	95.23Mpps
Service Port	4*PON port, 4*10GE/GE SFP+8GE
Redundancy Design	Built-in double power supply, including AC, double DC, AC+DC, single AC, single DC
Power Supply	AC: input100~240V 47/63Hz; DC: input36V~75V
Power Consumption	≤40W
Dimensions	440mm×44mm×311mm (Width x Depth x Height)
Weight (Full-Loaded)	≤3kg
Environmental Requirements	Working temperature: -10°C~55°C Storage temperature: -40°C~70°C Relative humidity: 10%~90%, non-condensing

ORDER INFORMATION

PRODUCT	PART NUMBER
EPON OLT, layer 3 , 8 PON ports , 4 ports 10G SFP	FO-7308X