LAN SYSTEM PRODUCTS

Patch Cord CAT6A FTP



DESCRIPTION

Ideally for high density cabling solution which reduces the amount of cable space required in each individual rack, increase cable pathway capacities saving you time, money and resources. The slim cable perfectly works for space at a premium.

FEATURES

- W / Tangle-free latch design
- Designed for high density environments (data centers and telecom rooms) where space is at a premium.
- Support PoE, PoE+, PoE++.
- 28AWG with OD: 4.7mm solid cable, only 60% size of traditional 26AWG patch cable.
- Better airflow and cooling performance.
- Length: 0.3m-20m; 0.5ft-60ft
- Color: Customized
- LSZH & PVC Jacket Available.
- Various boots available.

CONSTRUCTION

Sheath : PVC/LSZH	Conductor : Solid Copper
Test Limit : Fluke Channel	Cable OD : 4.7mm
Bandwidth : 500Mhz	Wiring Scheme : T568B/T568A
Length : 0.3m-20m; 0.5ft-60ft	PC Rated : 94-V2; 94-V0
Boot Type : Clear Boot	Frequency : 10Gbps
Connector : RJ45 8P8C 3U~50U	Pins : 8P
Plug : Tangle-Free Latch Plug	Multiple Certifications : UL,CE,SGS,ISO9001,RoHS,REACH
AWG : 28AWG	

ORDER INFOMATION	Color Code <u>X</u> = R W Y G B BB
PRODUCT	PART NUMBER
Cat6A FTP Patch Cord Slim, RJ45 to RJ45 1M	L-PC-US6AS-1-X
Cat6A FTP Patch Cord Slim, RJ45 to RJ45 2M	L-PC-US6AS-2-X
Cat6A FTP Patch Cord Slim, RJ45 to RJ45 3M	L-PC-US6AS-3-X

