

DIN RAIL POWER SUPPLY PRODUCTS

DIN RAIL POWER SUPPLY 75W



SPECIFICATION

Output	DC Voltage	24V	48V
	Rated current	3.2A	1.6A
	Current range	0-3.2A	0-1.6A
	DC power	76.8W	76.8W
	Voltage ADJ.range	24~28V	45~53V
	Voltage tolerance	±1%	±1%
	Ripple and noise	150mVp-p	240mVp-p
	Intet stability	±0.5%	±0.5%
	Load stability	±1%	±1%
	Input	AC voltage range	90~132VAC/170~264VAC 47~63Hz ; 120~370VDC
Current		1.8A/115V 0.9/230V	
Efficiency		85%	
AC Inrush current		Cold-start current 30A/115V 60A/230V	
Leakage current		< 3.5mA/240VAC	
Protection	Overload	105%~150% Type:pulsing hiccup shutdown Resete:auto recovery	
	Over voltage	58~65V	
Safety	Setup,rise,hold up time	1000ms,60ms,50ms/230V	
	Vibration	10~500Hz,2G 10min,/1 cycle	
	Withstand voltage	Input and output internal:1.5KvAc,input and enclosure:1.5KvAc,Output and enclosure:0.5KvAc	
Environment	Isolation resistance	Input and output internal:Input and enclosure,Output and enclosure:500VDC/100MΩ	
	Temperature coeffi cient	±0.03%/°C (0~50°C)	
	Working temperature and humidity	-10°C ~+60°C,20%~90%RH	
Other	Store temperature and humidity	-20°C ~+85°C,10%~95%RH	
	Overall dimension	55.5×125.2×100mm	
	Weight	0.55Kg	
Certificate	CE EMC Authenticate	EN55022:2010 EN61000-3-2:2006+AL:2009 EN61000-3-3:2008	
		EN55024:2010 EN55015:2006+AL2007+2009 EN61547:2009	



ORDER INFOMATION

PRODUCT	PART NUMBER
DIN RAIL POWER SUPPLY 75W, 24V, 3.2A	P-DR-75-24
DIN RAIL POWER SUPPLY 75W, 48V, 1.6A	P-DR-75-48

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com

