FIBER OPTIC ACCESSORIES

OPTICAL FIBER DISTRIBUTION FRAME (1296-1728)



DESCRIPTION

Focomm optical fiber distribution frame F-GPX09S is made of top quality steel and deformed aluminum alloy and treated with galvanizing, oxidation and electrostatic plastic spraying.

The frame has solid structure and pleasing appearance

FEATURES

- This frame reached YD/T778, YD/T694 standards and Chinese telecom enterprise product standard "Optical Fiber Main Distribution Frame (double-sided operation)".
- The frame is not only indoor terminal, but also double-sided optical fiber and pigtail equipment, contains the functions of optical fiber terminal distribution, transfer and storage, with the advantage of big capacity, convenient for both operation and maintenance, as well as plays a major role in optical fiber protection.
- Double-sided operation: Line modules at front side are used to outside cable fixing, stripping, splice and terminal; Row modules at back side are used to terminal equipments' pigtails and patch cords, left side fixing equipments' pigtails, as well as right side fiber-winding shaft.
- Line: SC or FC 12 cores adapter is installed on the drawer-type 12 cores integrated tray, and the tray is installed on the tray rack mount; Row: SC or FC 12 cores adapter is installed on the revolving 12 cores integrated tray, and the tray is installed in the 72 cores unit cabinet.
- Cables and fibers can be inlet from the top of the frame through separate entrances.
 Cable (fiber) entrances are protected by cable-protected ribbon and contain enough space for fiber passing.
- Multilayer horizontal fiber trays are installed on the row modules of the frame, convenient for frames combining.



OPERATION CONDITIONS

- Temperature -5°C ~ 60°C
- Humidity 90% at 30oC
- Air Pressure 70kPa 106kPa

ORDER INFOMATION

PRODUCT	PART NUMBER
Optical Fiber Distribution Frame 1296 Core 2000*880*300 (H*W*D)	F-GPX09S-1CW-1296
Optical Fiber Distribution Frame 1440 Core 2200*880*300 (H*W*D)	F-GPX09S-2CW-1440
Optical Fiber Distribution Frame 1728 Core 2600*880*300 (H*W*D)	F-GPX09S-3CW-1728





