

FIBER OPTIC ACCESSORIES

SIMPLEX/DUPLEX ADAPTOR SM/MM



FEATURES

- Compatible with FC, SC standard & ST. connector.
- PC ferrule with 20mm radius fast polishing.
- 8 degree angle PC ferrule with ultra low insertion loss.
- Low back reflection loss.
- Easy to handle Environmentally stable.
- Typical Insertion Loss Single-mode: 0.15dB, Multi-mode: 0.3dB.
- Typical Return Loss (*), Single-mode: 50dB, Multi-mode: 20dB
- Operating Temperature :-40~+75°C
- Storage Temperature: -55~+85°C
- Telecommunications.
- Local area network.
- Fiber optic sensors.
- Testing instruments.
- CATV



DESCRIPTION

The Fiber Optic adapter utilises a ceramic (Zirconia) sleeve for precise fiber ferrule alignment Multimode and Single mode version comes with a phosphor bronze sleeve. The adapter housing is mase of zine die-casting.

ORDER INFOMATION

| PRODUCT | PART NUMBER | |
|---------|-----------------------|-----------------|
| SM | ST Adaptor SM | F-AD -ST9 |
| | SC Adaptor Simplex SM | F -AD -SC9- SX |
| | SC Adaptor Duplex SM | F -AD -SC9 - DX |
| | LC Adaptor Simplex SM | F -AD -LC9 -SX |
| | LC Adaptor Duplex SM | F -AD -LC9-DX |
| | FC Adaptor SM | F -AD -FC9 |
| MM | ST Adaptor MM | F-AD -ST5 |
| | SC Adaptor Simplex MM | F -AD -SC5- SX |
| | SC Adaptor Duplex MM | F -AD -SC5- DX |
| | LC Adaptor Simplex MM | F -AD -LC5-SX |
| | LC Adaptor Duplex MM | F -AD-LC5-DX |
| | FC Adaptor MM | F -AD -FC5 |