LAN SYSTEM PRODUCTS

Patch Cord CAT6A UTP



DESCRIPTION

Ideally for high density cabling solution which reduces the amount of cable space required in each individual rack, increase cable pathway capacities saving you time, money and resources. The slim cable perfectly works for space at a premium.

FEATURES

- W / Tangle-free latch design on plugs
- Designed for high density environments (data centers and telecom rooms) where space is at a premium.
- Support POE, POE+, POE++.
- 28AWG with OD: 3.6mm, only 50% size of traditional 24AWG patch cable.
- Better airflow and cooling performance.
- Length: 0.3m-20m; 0.5ft-60ft
- LSZH & PVC Jacket Available.
- Various boots available.



CONSTRUCTION

Sheath: PVC/LSZH

Test Limit: Fluke Channel

Bandwidth: 500Mhz

Length: 0.3m-20m; 0.5ft-60ft

Boot Type : Clear Boot

Connector: RJ45 8P8C 3U~50U

Plug: Tangle-Free Latch Plug

AWG : 28

Conductor: Stranded Copper

Cable OD : 3.6mm

Wiring Scheme: T568B/T568A

PC Rated : 94-V2; 94-V0

Frequency: 10Gbps

Pins: 8P

Multiple Certifications: UL,CE,SGS,ISO9001,RoHS,REACH,ISO11801

ORDER INFOMATION















