

SURGE PROTECTOR PRODUCT

48VDC In: 10kA I_{max} 20kA Up: 400V Protection mode: +/-PE



FEATURES

- Built-in overheat circuit breaker. Failure window indication.
- Little leakage current, and large current capacity.
- Fast response time, low residual pressure.
- Pluggable modules to prevent the wrong connection device

APPLICATIONS

- Important equipment distribution box
- AC/DC power supply equipment
- Electronic information system cabinet



SPECIFICATIONS

Model	SP-PD20-48/DC
UC	75V
I _{Max}	10KA
I _n	20KA
U _p	≤300V
T _a	≤25ns
Work Status	Blank:ok Red:defect
T _u	-40 to 80°C
Connecting wire	2.5-6 mm ²
Ip Code	IP20
Dimension	90*68*18(*2/4)
Remote Signalization	Common Point:COM Normal Close: NC Normal Open:NO
Standards Compliance	IEC61643-11, IEC 61312-1, IEC 61312-3 (pending), IEC 61024-1, IEC 61000-4-5, IEC 61643-1-1, IEC 61643-1-2 (pending), IEC 62066 (pending), IEC 61643-2-1 (pending), IEC 61643-1, NFC 61740, VDE 0675, UL 1449, BS 6651