

DIN RAIL POWER SUPPLY PRODUCTS

DIN RAIL POWER SUPPLY 480W



SPECIFICATION

DC Output Voltage	48V
Output Voltage Range	±1%
Rated Output Current	5A
Output Current Range	0-5A
Wave And Noise	150mVp-p
Inlet Stability	±0.5%
Load Stability	±1%
DC Output Power	240W
Efficiency	85%
Adjustable Range For DC Voltage	43.2~52.8V%
AC Input Voltage Range	88~264VAC 47~63Hz; 120~370VDC
Input Current	3.5A/115V 1.8A/230V
AC Inrush Current	Cold-start current 30A/115V 60A/230V
Leakage Current	<3.5mA/240VAC
Overload Protection	105%~150% Type: pulsing hiccup shutdown Reset: tuto recovery
Over-Voltage Protection	54~60V
Temperature Coefficient	±0.03%/°c(0~50°c)
Setup, Rise, Hold Up Time	800ms, 40ms, 20ms/230VAC 800ms, 40ms, 20ms/115VAC
Vibration	10~500Hz, 2G 10min,/1cycle, Period for 60min, Each axes
Withstand Voltage	Input and output internal: Input and enclosure: 1.5KvAC Output and enclosure: 0.5KvAC
Isolation Resistance	Input and output internal: Input and enclosure, Output and enclosure: 500VDC/100MΩ
Working Temperature And Humidity	-10°c~+60°c(Refer to output derating curve), 20%~90%RH
Overall Dimension	125.5×125.2×100m
Weight	1.2Kgs 20PCS/14Kg/1.1CUFT
Safety Standards	Meet UL 1012 requirements (Not apply for the mark)
EMC Standards	Meet FCC PART 15 J Conduction class B



ORDER INFOMATION

PRODUCT	PART NUMBER
Power Supply, DIN Rail 480W, 48V, 5A	P-DR-480-48

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com

