

HDMI SPLITTER

4K@30Hz HDMI Splitter 1x2



OVERVIEW

The 1x2 HDMI Splitters uses a single HDMI source, accessing to multiple HDMI sinks. It allows one HDMI device to be split easily to 2 HDMI compatible monitors or projectors. In addition, it can be placed at the end of a long HDMI cable to regenerate the HDMI signal.

The resolution of this HDMI splitter can be up to 3840x2160/30Hz.

FEATURE

- Support HDMI 1.4b
- Support Full 3D
- Support HDMI resolution up to 3840x2160/30Hz
- Support the max baud rate of 3.4G and max bandwidth of 340Mhz
- Support deep color 8/10/12bit
- Support input up to 8 metres AWG26 HDMI standard cable length, output up to 8 metres AWG26 HDMI standard cable length
- Displaying single source, multi-output high-definition signal source from DVD player AV receiver, set-top box
- 5V/1A power adapter



APPLICATIONS



FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com



SPECIFICATIONS

HDMI version	HDMI 1.4b
HDMI resolution	up to 3840x2160/30Hz
Support video format	8/10/12bit Deep color
Support audio format	DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD
Max bandwidth	340MHz
Max baud rate	3.4Gbps
Input cable distance	≤8m AWG26 HDMI standard cable
Output cable distance	≤8m AWG26 HDMI standard cable
HDMI input	1 HDMI
HDMI output	2 HDMI
Max working current	500mA
Specifications of power adapter	input AC (50Hz, 60Hz) 100V-240V; output: DC5V/1A
Operating Temperature range	(-15°C to +55°C)
Operating Humidity range	5 to 90%RH (No Condensation)
Dimension (L x W x H)	128x53x23.5 (mm)
Weight	139g

ORDER INFORMATION

PRODUCT	PART NUMBER
4K@30hz HDMI Splitter 1x2	MD-4KHDS-0102