

HDMI SPLITTER

4K@30hz HDMI Splitter 1x8



OVERVIEW

The 1x8 HDMI Splitter uses a single HDMI source, accessing to multiple HDMI sinks. It allows one HDMI device to be split easily to eight HDMI compatible monitors or projectors. In addition it can be placed at the end of a long HDMI cable to regenerate the HDMI signal. The resolution of this hdmi splitter can be up to 3840x2160/30Hz.




FEATURE

- Plug and play, easy to operate
- Transmission distance up to 20M

SPECIFICATIONS

HDMI resolution	up to 3840x2160/30Hz
Support video format	8/10/12bit deep color
Support audio format	DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD
Max bandwidth	340MHz
Max baud rate	3.4Gbps
Input cable distance	(1080p resolution) ≤10m,(4K resolution)≤5m AWG26 HDMI standard cable
Output cable distance	(1080p resolution) ≤20m,(4K resolution)≤10m AWG26 HDMI standard cable
Max working current	0.4A
Power adapter format	input AC (50HZ, 60HZ) 100V-240V; output: DC5V/1A
Operating Temperature range	(-15 to +55°C)
Dimension (L x W x H)	276x136x24 (mm)
Weight	660g

APPLICATIONS



Audio-visual conference




TV market



Home theater



HDMI Cable (20M)




FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com



PHYSICAL INTERFACE DIAGRAM



CONNECTION AND OPERATION

- 1: connect the HD source to the splitter input with one hdmi cable;
- 2: connect the splitter output to the displays with 8 hdmi cables;
- 3: connect 5V/1A power adapter to the splitter;

ORDER INFOMATION

PRODUCT	PART NUMBER
4K@30hz HDMI Splitter 1x8	MD-4KHDS-0108