

FIBER OPTIC ACCESSORIES

MTRJ SM/MM CONNECTOR



FEATURES

- The style is diverse, the interface is complete
- Low insertion loss and added loss
- Height of attenuation
- High back loss, small volume, light weight
- High stability, high reliability
- Mechanical performance: IEC 874-18.



APPLICATION

- Optical fiber communication systems engineering
- Fiber optic data communication network
- Fiber CATV engineering
- Other optical technology tests

SPECIFICATION

Applicable connector type.	MTRJ
Optical fiber type	SM/MM
Test the wavelength	1310nm~1550nm
Insertion loss	Typical value ≤ 0.15 , maximum ≤ 0.50
Return Loss	≥ 35 dB
Repeatability	≤ 0.10 dB
Interchangeability	≤ 0.10 dB
Durability	500 times plug
Suitable for optical cable diameter	2.0mm
Working temperature	-20°C to +70°C
Storage temperature	-40°C to +85°C

PRODUCT PARAMETERS

Type	SM-UPC		MM-UPC	
	Typical	MAX	Typical	MAX
Insertion loss	≤ 0.1	≤ 0.3 dB	≤ 0.05	≤ 0.3 dB
Return loss	≥ 50 dB		≥ 30 dB	
Ferrule hole sizes	125.2-126.2um		125-128um	

ORDER INFORMATION

PRODUCT	PART NUMBER
MTRJ Connector Simplex, SM	F-CN-MTRJ9-SX
MTRJ Connector Duplex, SM	F-CN-MTRJ9-DX
MTRJ Connector Simplex, MM	F-CN-MTRJ5-SX
MTRJ Connector Duplex, MM	F-CN-MTRJ5-DX