
FIBER OPTIC ACCESSORIES

SPLICE TRAY 24 CORE



FEATURES

- ABS material used ensures the body strong and light
- The fusing distribution board of the unit box is double layer structure, integrating the fusing and distribution into one unity.
- 24-fiber splice trays
- Protect and manage heat shrink style spliced fibers
- Heat shrink splice holder and sleeves included
- Clear cover allows viewing or inspection of fibers without having to remove cover
- Use for single-mode or multimode fiber
- Durable injection-molded plastic trays and covers
- Longer bending radius for fiber, Easy operation of fiber/pigtails
- Easily disposed for particular needs
- Suitable for ribbon or non-ribbon optical fiber cable



DESCRIPTION

Splice tray is used in optical distribution frame, distribution box, and splice closures, which is engineered for use with indoor or outdoor splice hardware with both loose tube and tight-buffered optical cable designs. The compact splice cassettes designed for simple, cost effective low and mid-sized fiber splicing applications. Each cassette is supplied with splice holders that secure and protect both fusion and mechanical splices; also the top cover is included.

DIMENSIONS AND CAPABILITY

OPERATION CONDITIONS

Dimensions (W*H*D)	224mm*114mm*17mm per unit
Capacity	24 cores per unit
Optional Accessories	Heat Shrink Tubes, Heat
	Shrink Splice Holder
Material	ABS 1.0mm
Max diameter of entry cable	4.0mm
Weight	0.10 KG per unit

Temperature	$-40^{\circ}\text{C} \sim 55^{\circ}\text{C}$
Sealing performance	Remain unchanged for72 hours
	on pressure 70kpa
Air Pressure	70kPa – 106kPa
Tensile Strength	>1000N
Compressive Strength	Withstand 2000N/10Cm ² in 1min
Sleeve galvanize	1.0 mm.

SHIPPING INFORMATION

Package Contents	Splice Tray Base with Splice Holder; Splice Tray Cover
Package Dimensions(W*H*D)	270mm*150mm*65mm per unit
Material	Carton box
Weight	0.65 KG per unit

ORDER INFOMATION

PRODUCT	PART NUMBER
Splice Tray 24 Cores	F-Tray-24

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict,Bang Khen District Bangkok 10220 Email : info@focomm-cabling.com www.focomm-cabling.com





