

FIBER OPTIC ACCESSORIES

HYBRID ADAPTOR SIMPLEX/DUPLEX ADAPTOR SM/MM



FEATURES

- Discordia,ANSI,TIA/EIA,NTTandJIScompliance.
- High precision alignment.
- Good repeat ability.
- ultra low insertion loss.
- Low back reflection loss.
- Easy to handle Environmentally stable.
- Good change ability.
- Good temperature stabilization.
- Durability: 1000 matings



APPLICATION

- Telecommunications.
- Local area network.
- Use for fusion splice
- Fiber optic sensors.
- CATV
- Testing/Measurement Instruments Fiber To the Home

APPLICATION

- TIA/EIA-568-C.3, ISO/IEC 11801, IEC 61754
- Telcordia GR-326-CORE
- RoHS Compliant

PARAMETER

Item NO.	Test Item	Unit	Standard & Requirement
1	Insertion Loss (dB)	dB	≤ 0.20 dB
2	Repetitiveness (dB)	dB	≤ 0.10 dB
3	Interchangeability (dB)	dB	≤ 0.20 dB
4	Plug times	times	>500
5	Tensile Strength	G	200~600G
6	Operating temperature	Celsius	-40---+85 Celsius
7	Storage temperature	Celsius	-40---+110 Celsius
8	Humidity	Celsius	95%RH (Non-Packaging)

ORDER INFOMATION

PRODUCT	DESCRIPTION	PART NUMBER
SM	ST to FC Adapter, SM	F-HAD-STFC9
	SC to FC Adapter, SM	F-HAD-SCFC9
	ST to SC Adapter, SM	F-HAD-STSC9

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com

