

RACK AND CABINET PRODUCT

Power Bar Lighting Switch



DESCRIPTION

PDU series are modularized and multi-functional power distribution units exclusively for cabinet. The series products are designed & developed according to international standard, and obtained several invent patent, and are made up of many standards of power socket modules, controlled function module, protecting function module, surge protector module, channel surge protector module, digital AC amperemeter module, creepage protector module, etc. The products are applied to 482.6mm (19") standard cabinet & nonstandard cabinet, and electronic & electric equipment of high-tech fields. Modularized and multi-functional power distribution unit is with proven & novel structure, international advanced technology, safe & reliable quality, easy installation and wide usage



FEATURE

- Modularized structure Design and manufacturing of the product is arranged in a modularized way.
- Diversified socket system The product is equipped with supply socket modules meeting different systems and standards in the world, which puts the product in a rather advantageous position to satisfy clients in each country or region.
- Diversified input characteristics The product can be tailored to satisfy specific requirements on the cabinet in terms of its power input. The product is designed with diversified power input methods and equipped with plug cables specified in different systems or standards.
- Reliable output characteristics Sleeves or parts subordinate to a socket are made with phosphor bronze, the material famous for its elasticity, wear resistance, diamagnetism and corrosion resistance. The product is a result of precision work and integral impact and forming, which ensures a reliable contact and a single-pole pull-and-plug life at 5000 times above, a safe and reliable operation, no loosening, no strike, and reliable electric conductivity and connectivity.
- Internationally prevailing system and standard The product, a result of design and manufacturing process meeting applicable standards in the world, finds particular applications in standard cabinets 482.6mm [19"] in terms of its installation, application and other technical matters.



Universal Outlet
w/Eye Shutter




Overload Protection
w/LED Indicator




Lighting Switch
w/Guard



PDU Bracket Kit
for Vertical Mount



Horizontal Mounting



Vertical Mounting
w/PDU Bracket Kit

DESCRIPTION

Input plug	BS1363 250VAC
Cable Spec.	3×1.5mm ² ×2M
Output unit	4,6,12
Function optional	double poles with light switch 16A
Rated input voltage	110/220VAC 50/60Hz
Max load current	13A
Product size	483X44.4X44.4mm 19"1U
Cover material	Aluminum alloy (plastic)

ORDER INFORMATION

PRODUCT	PART NUMBER
4 Power Bar Universal, Lighting SW and Protection, Cable 2m	R-PWB-LP-04
6 Power Bar Universal, Lighting SW and Protection, Cable 2m	R-PWB-LP-06
12 Power Bar Universal, Lighting SW and Protection, Cable 2m	R-PWB-LP-12