

# RACK AND CABINET PRODUCT

## WALL CABINET



### FEATURE

- Exquisite design with precise dimension and craftsmanship.
- International popular smoky-gray glass front door.
- Easily be mounted on wall, or placed on floor after installed castor or feet.
- Loading capacity: 60KG.
- Top and bottom wiring channel could be closed.
- Removable front door and side panel, easily installing and maintaining
- Surface finish: Degreased, acid cleaned, phosphoric, water cleaned, electro-static powder coating, meet ROHS standard.
- Optional color: black/gray
- Optional accessories

### MATERIALS

Galvanized Cool rolled steel

Thickness: Vertical rail: 2mm

Else in 1.2mm

Tempered smoky-gray glass with thickness of 5mm.

Electro static powder coating.

Including green-yellow ground wire size 2.5mm.

### APPLICATION

Widely used in network system, educational system, broadcasting system and telecommunication system. Suitable for placing server computer and precision electronic equipment.

### STANDARD

Comply with ANSI/EIARS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92 standard, IEC 60297, ANSI/EIA-310D-1992(Rev, EIA-310-C) , IEC 60297-1, IEC 60927-2Compatible with metric ETSI and 19 inch international standard, ROHS standard.

FIXED MODEL (WCF)



SWING MODEL (WCS)



PERFEORRATE MODEL (WCP)



### ORDER INFORMATION

□ = Fixed Model

□ = Swing Model

□ = Perfeorrate Model

(Capacity)

12U ( H = 64 cm)  
9U ( H = 51 cm)  
6U ( H = 38 cm)

(Depth)

40 = 400mm  
50 = 500mm  
60 = 600mm

COLOR

BB = Black(RAL9004)

BG = Gray(RAL7044)

