

# POE SWITCH SYSTEM PRODUCTS

Web Smart managed POE switch 8x 10/100/1000M RJ45 ports Built-in 75W



## OVERVIEW

**SW-8GP** is a Gigabit Web smart PoE switch equipped with 8 10/100/1000Mbps RJ45 adaptive ports. 8 RJ45 support PoE standard IEEE802.3af, IEEE802.3at. It has good network adaptability.



## FEATURE

- Supports IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3az, IEEE802.3af, IEEE802.3at.
- Provide 8 10/100/1000Mbps auto-sensing RJ45 ports.
- 8 POE ports support 802.3af/at, per port up to 30W with 112.8W Poe budget.
- Dynamic LED lights provide real-time work status display and basic fault diagnosis.
- Auto-negotiation on each port senses the link speed of a network device (either 10, 100, or 1000 Mbps) and intelligently adjusts for compatibility and optimal performance.
- CE, ROHS, FCC, UKCA PoE 8 Ports Switch Gigabit Ethernet Ports, 802.1Q VLAN

## APPLICATIONS

### Value-Added Features Bring Unexpexted Experiences

#### QoS for a Lag-Free Experience

Ensures smooth traffic for latency-sensitive applications, such as voice and video

#### IGMP Snooping forMulticast Optimization

Ensures a better network experience, especially for applications like IPTV, by optimizing multimedia traffic delivery.

#### VLAN for Security

Helps to create a network with higher security and better overall performance by dividing the network into smaller groups

## SPECIFICATIONS

Power Supply	44-57V DC
Standards	IEEE 802.3i,802.3u,802.3ab,802.3x,802.3at,802.3af,802.3z
Ports	8 10,100,1000Mbps RJ45 and PoE ports
Indicators	8 electrical port speed indicators, 8 electrical port link/act indicators, power input indicator
Network medium	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5e, 6 cable (maximum 100m) 1000Base-X:MMF,SMF
Dimensions	160 * 95 * 30 mm
PoE port	8 802.3at/af standard POE
PoE Pin Definition	1/2(+),3/6(-)
PoE power	112.8W
Total power	118.8W
Transfer Method	Store-and-Forward
MAC Address Table	4K
Switching Capacity	16Gbps
Packet Forwarding Rate	11.904Mpps
Packet Buffer	1.5Mbit
Jumbo Frame	9KBytes
Environment	Operating Temperature: 0°C ~45°C (0°F~113°F) Storage Temperature: -40°C ~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing
Warranty	2 Year

## ORDER INFORMATION

PRODUCT	PART NUMBER
Web Smart managed POE switch 8x 10/100/1000M RJ45 ports Built-in 75W	SW-8GP